

# **Blue Water Fisheries Revised Site Analysis**









NOAA Office for Coastal Management NOAA National Centers for Coastal and Ocean Science James.Morris@noaa.gov



# Background / Farm Requirements

- Fall 2019 Initial meetings with NCCOS and BWF
- Nov 2019 Oct 2020 Spatial Analysis and iterations completed
- Nov 2020 Final Report Pre-Applications meetings
- Jan-Mar 2023 Updated spatial analysis

CASS Request Farm Response (2019/2020)			
Preferred Ports	Portsmouth, Rye Harbor, Hampton Harbor, Newburyport		
Maximum distance from port/shore	≤ 12 nautical miles		
Gear depth	≥ 52 and ≤ 90 m		
Farm Footprint	265 acres (107 ha)		
Seawater temperature	10 to 16 °C at 15-20 m depth		
Significant wave height	< 5 m		


Farm Orientation Perpendicular to prevailing currents




### **AOI** Revisions 2023

Cod Whaleback area now considered a constraint


Updated Data Layers and Methods used





### **AOI** Revisions 2023


Bathymetry 52 - 90 m





## **Suitability Model Design**

- Four submodels and constraints model
- Equal weights for all data and submodels
- Geometric mean used for calculating scores






# Scoring data to standardized range (0-1)

## Categorical data

Layer not compatible = 0 Layer has uncertain compatibility = 0.5 Layer not present = 1

Example Data	Score
Hard Bottom Habitat	0
Military Operating Area	0.5
Oil and Gas Pipelines (500 m setback)	0

### Numerical/Continuous data






## **Updated Suitability Model**

Submodel	Data Layer	Score
Constraints	Cod Industry Based Surveys 2 km	0
Constraints	ENC Wrecks	0
National Security	Unexploded Ordnance	0.5
National Security	Boston Operating Area	0.5
Industry	AIS SUM 2017-2021	zmf
Fishing	VMS SUM 2009-2019	zmf
Logistics	Sediment grain size (Smaller is preferred)	zmf
Logistics	Distance to inlet (Close is better)	Linear
Logistics	Depth (Shallower is better)	Linear


# Constraints data Layers

Cod Industry Based Surveys

**ENC Shipwrecks** 




## Constraints Submodel




# National Security Data

Boston Military Operating Area

Unexploded Ordnances




## National Security Submodel






## **Industry Data**

Sum of AIS All Vessel Type Transits 2017-2021



<sup>\*</sup>Note Vessels without AIS transponders not represented (i.e. small fishing vessels)

# Industry Submodel






### **Fisheries Data**

VMS (all gear types)

Sum 2009-2019

Tracks created from points that were < 1 mi apart and <1 hr in time difference


All data used in model, but not displayed due to confidentiality



Cells with < 3 unique vessels are not displayed



## Fisheries Submodel



Cells with < 3 unique vessels are not displayed




## Logistics Submodel


Distance from Inlets

Bathymetry


Sediment grain size



## Calculation of Final Suitability Model



## Final Suitability







# Cluster Analysis

584 m search distance used (265 ac farm)

p < 0.05 (CI 95%)



# Comparison to Old Analysis






## **Next Steps**

Review Model and make any adjustments to parameters


Identify and rank potential farm sites

Characterize and review potential farm sites


#### Original Model with Logistics Submodel




#### New Model without Logistics Submodel




#### Original Model with Logistics Submodel




#### New Model without Logistics Submodel



## **Precision Siting Overview**





## **TOPSIS** Analysis

Data Layer	Score
Option perpendicular to current	Linear
AIS SUM 2017-2021	zmf
VMS SUM 2009-2019	zmf

Identify the top three ranked sites that do not overlap

### **TOPSIS Calculations**

$$S_i^+ = \sqrt{\sum_{j=1}^n (v_{ij} - v_j^+)^2}$$

Calculates distance from each alternative site to the most positive solution

$$S_i^- = \sqrt{\sum_{j=1}^n (v_{ij} - v_j^-)^2}$$


Calculates distance from each alternative site to the most negative solution

TOPSIS Score = 
$$\frac{s_i^-}{(s_i^- + s_i^+)}$$

Calculates the TOPSIS score from each alternative site

 $S_i^-$ =Negative Solution  $S_i^+$  = Positive Solution  $v_{ij}$  = Variable i of j  $v_i^+$  = Most Positive Score for Variable i  $v_i^-$  = Most Negative Score for Variable i








## **VMS** Transits

## -70.58° -70.5° 0 100 km State Water Boundary BWF Revised AOI VMS Transits (2009-2019) Scale: 1:125,000 USA Contiguous Albers Equal Area Conic (EPSG:102003) Service Layer Credits: Esri, HERE, Garmin, (c) OpenStreetMap contributors, and the GIS user community Map intended for planning purposes only: Not intended for navigational purposes National Centers for Coastal Ocean Science

## **AIS Transits**








# Potential Options

3850 options evaluated

All options are 265 ac (1508 m x 711 m)

All options rotated by 10°


All options spaced by 71m (1/10 of width)



# Ranked Options

Top Ranking options with no overlap with other options

Total of 6 identified, top three chosen for further review




## **TOPSIS Option Ranking**

Rank	Option	AIS/265ac	VMS/265ac	Degrees from Ideal	TOPSIS Score
1	1-1	55	1871	79.5	0.64
2	2-1	66	1966	0.5	0.63
3	2-2	75	2124	0.5	0.58
4	2-3	67	3078	40.5	0.45
5	2-4	69	3138	40.1	0.42
6	2-5	47	4364	109.5	0.42

## Ranks for Options


Option	AIS Rank	VMS Rank	Degrees from ideal Rank	TOPSIS Score	Rank
1-1	2	1	5	0.64	1
2-1	3	2	1	0.63	2
2-2	6	3	2	0.58	3
2-3	4	4	4	0.45	4
2-4	5	5	3	0.42	5
2-5	1	6	6	0.42	6

## VMS






## AIS





## Bathymetry






# Comparison to Original analysis

None of the newly proposed options are near any location where Cod spawning has been recorded\*

\*Does not mean cod spawning could not occur in any of the new options




### **Site 1-1**


Only site in North Cluster

Near potential Hardbottom

Shallowest of sites

Lower vessel fishing effort than most other sites





## **Site 2-1**

Ideal site between high vessel traffic and high fishing transits

Deeper site, perpendicular to current

NNE

ENE

SE


NNW

WNW

W

WSW

SW



## **Site 2-2**

Ideal site between high vessel traffic and high fishing transits

Deeper site, perpendicular to current

ENE


SE

WNW


WSW

SW

SSW



# Distance to ports





# Spacing of 2-1 and 2-2

Adjustment of spacing between sites could be performed if needed

